


## CUBE20S PROFIBUS BUS NODE

Bus nodes  
PROFIBUS DP

[Link til artikel](#)

### Billede



Produktet kan afvige fra billedet

### Godkendelser



**Mere information**



**PROFIBUS**

Addressing Address switch 1...125

**Connections**

Fieldbus	PROFIBUS 12 Mbit/s; SUB-D9
Internal system connection	4 × Spring clamp plug-in terminals, max. 1.5 mm <sup>2</sup> (max. 10 A)
Sensor-system/actuator supply	4 × Spring clamp plug-in terminals, max. 1.5 mm <sup>2</sup> (max. 10 A)

**Module supply**

Operating voltage	24 V DC (EN 61131-2)
Current consumption	max. 95 mA

**General data**

Protection	IP20
Connection	Spring clamp plug-in terminals: max. 1.5 mm <sup>2</sup> (max. 10 A)
Mounting method	DIN-rail mountable (EN 60715)
Temperature range	0...+60 °C (storage temperature -25...+70 °C)
Dimensions H × W × D	109×48.5×76.5 mm

**Cube system**

Module capacity	max. 64
I/O capacity	max. 244 Byte (Input), max. 244 Byte (Output)

**Output**

Output voltage (I/Os /Backplane)	24 V DC/5 V DC
Output current (I/Os /Backplane)	10 A/3 A

**Diagnostic**

Communication status	via LED
Diagnostic via LED	per module and channel
Diagnostic via BUS	per module
Monitoring - under voltage	no
Monitoring - no voltage	yes
Short-circuit and overload	yes
Actuator warning	no

**Commercial data**

country of origin	TH
customs tariff number	85389099
EAN	4048879422307
eClass	27242608
Pakke-enhed	1